

BA220/BA220+

Suitable Conditions

Medium and long mileage trucks running on paved and unpaved roads

- ☑ Ultra Wear Resistance
- ☑ High Stability on Handling
- ☑ High Load Capacity



● suitable



Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
VN	11R22.5	16	146/143K	8.25	3000	2725	6610	6005	830	830	120	120	17.5	1054	279
CN	11R22.5	16	148/145L	8.25	3150	2900	6940	6395	850	850	123	123	17.5	1054	279
CN & VN	12R22.5	18	152/149K	9.00	3550	3250	7825	7165	930	930	135	135	18.0	1085	300
CN	13R22.5	20	156/150L	9.75	4000	3350	8820	7390	900	900	130	130	18.0	1124	320
VN	13R22.5	20	156/150K	9.75	4000	3350	8820	7390	900	900	130	130	18.0	1124	320
VN	11R24.5	14	146/143K	8.25	3000	2725	6610	6005	720	720	105	105	17.5	1104	279
VN	11R24.5	16	149/146K	8.25	3250	3000	7160	6610	830	830	120	120	17.5	1104	279
CN	295/80R22.5	18	152/149K	9.00	3550	3250	7825	6945	900	900	130	130	18.0	1044	298
VN	*295/80R22.5	18	154/149K	9.00	3750	3250	8270	7160	850	850	125	125	17.0	1044	298
CN	315/80R22.5	20	156/153L	9.00	4000	3650	8820	8050	850	850	125	125	17.0	1076	312
VN	315/80R22.5	20	156/150(154/150)L(M)	9.00	4000	3350	8820	7390	850	850	125	125	17.0	1076	312

*295/80R22.5 applied to BA220+

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs