

# BA267

## Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ☑ Tear Resistance
- ☑ Reduce Stone Trapping
- ☑ High Load Capacity



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	215/75R17.5	16	135/133L	6.00	2180	2060	4805	4540	860	860	125	125	15.0	773	211
CN	235/75R17.5	18	143/141L	6.75	2725	2575	6005	5675	860	860	125	125	15.0	797	233
CN	265/70R19.5	18	143/141J	7.50	2725	2575	6005	5675	900	900	130	130	15.0	867	262
VN	275/80R22.5	18	149/146L	8.25	3250	3000	7160	6610	900	900	130	130	18.5	1012	276
VN	295/80R22.5	18	152/149L	9.00	3550	3250	7825	6945	900	900	130	130	18.0	1044	298
VN	10.00R20	18	149/146K	7.5	3250	3000	7165	6610	930	930	135	135	16.0	1054	278
VN	11.00R20	18	152/149K	8.0	3550	3250	7830	7170	930	930	135	135	17.0	1096	293

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs