

BD175

Suitable Conditions

Medium and long mileage trucks running on paved and highway roads

- ☑ Low Heat Generation
- ☑ High Wear Resistance
- ☑ Excellent Grip
- ☑ Economy and Environment Friendly



● suitable

Origin	Size	PR	LI/SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	11R22.5	16	148/145L	8.25	3150	2900	6940	6395	850	850	123	123	20.0	1059	279
CN & VN	11R22.5	16	146/143K	8.25	3000	2725	6610	6010	850	850	123	123	20.0	1065	279
CN	12R22.5	18	152/149K	9.00	3550	3250	7825	7165	930	930	135	135	20.0	1096	300
VN	12R22.5	18	152/149L	9.00	3550	3250	7830	7160	930	930	135	135	20.0	1096	300
CN	13R22.5	18	154/151K	9.75	3750	3450	8270	7605	830	830	120	120	20.5	1124	320
CN & VN	205/75R17.5	14	124/122L	6.00	1600	1500	3525	3310	750	750	110	110	15.0	753	204
CN & VN	215/75R17.5	16	135/133L	6.00	2180	2060	4805	4540	860	860	125	125	15.0	767	211
CN & VN	235/75R17.5	18	143/141L	6.75	2725	2575	6005	5675	860	860	125	125	15.0	797	233
CN	225/70R19.5	14	128/126L	6.75	1800	1700	3970	3750	760	760	110	110	15.0	811	226
CN & VN	245/70R19.5	18	144/142J	7.50	2800	2650	6175	5840	900	900	130	130	15.5	839	248
CN	265/70R19.5	18	143/141J	7.50	2725	2575	6005	5675	900	900	130	130	15.5	867	262
CN	255/70R22.5	16	140/137L	7.50	2500	2300	5510	5070	830	830	120	120	15.5	930	255
VN	275/80R22.5	16	146/143L	8.25	3000	2725	6610	6005	830	830	120	120	22.0	1012	276
CN & VN	295/80R22.5	18	152/149M	9.00	3550	3250	7825	7165	900	900	130	130	22.0	1044	298
VN	315/70R22.5	18	156/150L	9.00	4000	3350	8820	7385	900	900	130	130	20.0	1014	312
CN & VN	315/80R22.5	20	156/153L	9.00	4000	3650	8820	8045	850	850	125	125	23.0	1076	312
VN	315/80R22.5	20	156/150(154/150)L(M)	9.00	4000	3350	8820	7390	850	850	125	125	23.0	1076	312
CN	315/80R22.5	22	158/156K	9.00	4250	4000	9370	8820	900	900	130	130	23.0	1076	312

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs