

# BD189

## Suitable Conditions

Short mileage vehicles running on unpaved roads

- Cut Resistance
- Excellent Grip
- Avoid Damage on Tread



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN & VN	11R22.5	16	148/145G	8.25	3150	2900	6940	6395	850	850	123	123	23.5	1065	279
CN & VN	11R22.5	18	149/146G	8.25	3250	3000	7160	6610	900	900	130	130	23.5	1065	279
CN	12R22.5	18	152/149G	9.00	3550	3250	7830	7160	930	930	135	135	23.5	1096	300
CN	12R22.5	18	152/149K	9.00	3550	3250	7830	7160	930	930	135	135	23.5	1096	300
CN	13R22.5	18	156/150G	9.75	4000	3350	8820	7390	875	875	125	125	23.5	1136	320
CN	13R22.5	20	156/150G	9.75	4000	3350	8820	7390	875	875	125	125	23.5	1136	320
CN & VN	11R24.5	16	149/146G	8.25	3250	3000	7160	6610	830	830	120	120	23.5	1110	279
CN	275/70R22.5	16	148/145J	8.25	3150	2900	6940	6395	900	900	130	130	23.5	958	276
CN & VN	295/80R22.5	18	152/149J	9.00	3550	3250	7830	7160	900	900	130	130	23.5	1044	298
CN	315/80R22.5	20	157/154G	9.00	4125	3750	9090	8270	900	900	130	130	23.5	1076	312
CN	315/80R22.5	22	167/164G	9.00	5450	5000	12000	11000	950	950	140	140	23.5	1076	312
CN	12.00R20	20	156/153J	8.5	4000	3650	8820	8050	900	900	130	130	23.5	1136	315
CN	12.00R20	22	158/155J	8.5	4250	3875	9370	8540	970	970	140	140	23.5	1136	315

S=Single D= Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈ 2.2lbs