

# BD218

## Suitable Conditions

Medium and Short mileage vehicles running on paved and unpaved roads

- ☑ Tear Resistance
- ☑ Excellent Grip
- ☑ High Load Capacity



● suitable



Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	9.5R17.5	18	143/141K	6.75	2725	2575	6005	5675	875	875	125	125	16.5	850	240
CN & VN	11R22.5	16	148/145L	8.25	3150	2900	6640	6395	850	850	123	123	22.5	1059	279
CN	12R22.5	18	152/149K	9.00	3550	3250	7830	7160	930	930	135	135	20.0	1096	300
VN	11R24.5	16	149/146L	8.25	3250	3000	7160	6610	830	830	120	120	22.0	1110	279
CN	225/80R17.5	18	123/122L	6.75	1550	1500	3415	3305	700	700	102	102	14.0	811	226
CN	265/70R19.5	18	143/141K	7.50	2725	2575	6005	5675	900	900	130	130	15.0	867	262
CN	275/70R22.5	18	148/145M	8.25	3150	2900	6940	6395	900	900	130	130	17.0	958	276
CN	295/80R22.5	18	152/149L	9.00	3550	3250	7825	7165	900	900	130	130	19.0	1044	298
VN	11.00R20	18	152/149K	8.0	3550	3250	7830	7170	930	930	135	135	19.5	1096	293
VN	12.00R20	20	156/153K	8.5	4000	3650	8820	8050	900	900	130	130	21.0	1136	315
CN & VN	325/95R24	22	162/160K	9.00	4750	4500	10500	9920	850	850	125	125	20.0	1228	325

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs