

# BD260

## Suitable Conditions

Medium and Short mileage vehicles running on paved and unpaved roads

- Tear Resistance
- Excellent Grip
- High Load Capacity



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	7.00R16LT	14	118/114L	5.50F	1320	1180	2910	2600	770	770	110	110	14.0	785	200
CN	7.50R16LT	14	122/118L	6.00G	1500	1320	3310	2910	770	770	110	110	16.0	815	215
CN	8.25R16LT	16	128/124K	6.50H	1800	1600	3970	3530	770	770	110	110	16.0	865	235
CN	8.25R20	16	139/137K	6.5	2430	2300	5360	5070	930	930	135	135	17.5	974	236
VN	10.00R20	18	149/146K	7.5	3250	3000	7165	6610	930	930	135	135	18.5	1065	278
VN	11.00R20	18	152/149K	8.0	3550	3250	7830	7170	930	930	135	135	19.5	1096	293
VN	12.00R20	18	154/151K	8.5	3750	3450	8270	7610	830	830	120	120	21.0	1136	315

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs