

BD280

Suitable Conditions

Dump truck tire drive position tire used for medium and short distances on mixed road surfaces

- ☑ Tear Resistance
- ☑ Anti Damage on Tread
- ☑ Strong Constructure



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN & VN	11R22.5	16	148/145K	8.25	3150	2900	6945	6395	840	840	120	120	19.0	1059	279
CN & VN	12R22.5	18	152/149K	9.00	3550	3250	7825	7165	930	930	135	135	20.0	1096	300
CN & VN	13R22.5	20	156/150J	9.75	4000	3350	8820	7390	900	900	130	130	20.0	1124	320
CN	295/80R22.5	18	152/149K	9.00	3550	3250	7825	7165	900	900	130	130	18.0	1044	298
CN	315/80R22.5	20	156/153K	9.00	4000	3650	8820	8045	850	850	125	125	20.5	1076	312
VN	315/80R22.5	20	156/150(154/150)J(K)	9.00	4000	3350	8820	7390	850	850	125	125	20.5	1076	312
VN	315/80R22.5	22	167/164G	9.00	5450	5000	12000	11000	950	950	140	140	20.5	1076	312

S=Single D= Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs