

# BLR01

## Suitable Conditions

Medium and long mileage trucks running on paved and unpaved roads

- ☑ Good Handling
- ☑ Adapt to Various Road Conditions
- ☑ Excellent CPK



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN & VN	11R22.5	16	148/145M	8.25	3150	2900	6945	6395	840	840	120	120	16.0	1054	279
CN	12R22.5	18	152/148K	9.00	3550	3150	7825	6945	850	850	125	125	16.5	1085	300
CN	13R22.5	20	156/150J	9.75	4000	3350	8820	7390	900	900	130	130	16.0	1124	320
CN	295/80R22.5	18	152/149L	9.00	3550	3250	7825	7165	900	900	130	130	17.5	1044	298
CN	315/80R22.5	20	156/153K	9.00	4000	3650	8820	8045	850	850	125	125	14.0	1076	312
CN	7.00R16LT	14	118/114L	5.50F	1320	1180	2910	2600	770	770	110	110	11.5	775	205
CN & VN	7.50R16LT	14	122/118L	6.00G	1500	1320	3310	2910	770	770	110	110	12.5	805	215
CN	8.25R16LT	14	126/122L	6.50H	1700	1500	3750	3310	670	670	97	97	12.5	855	235
CN	8.25R16LT	16	128/124L	6.50H	1800	1600	3970	3530	770	770	110	110	12.5	855	235
CN	9.00R20	16	144/142K	7.0	2800	2650	6170	5840	900	900	130	130	15.0	1019	259
CN	10.00R20	16	146/143K	7.5	3000	2725	6610	6010	830	830	120	120	16.0	1054	278
CN	10.00R20	18	149/146K	7.5	3250	3000	7165	6610	930	930	135	135	16.0	1054	278
CN	11.00R20	16	150/147K	8.0	3350	3075	7385	6780	830	830	120	120	16.5	1085	293
CN	11.00R20	18	152/149K	8.0	3550	3250	7830	7170	930	930	135	135	16.5	1085	293
CN	12.00R20	18	154/151K	8.5	3750	3450	8270	7610	830	830	120	120	17.0	1125	315
CN	12.00R24	20	160/157K	8.5	4500	4125	9920	9100	900	900	130	130	15.5	1226	315
VN	325/95R24	22	162/160K	9.00	4750	4500	10500	9920	850	850	123	123	15.5	1228	325

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs