

# CATCHFORS M/T II



M+S

## CATCHFORS M/T II M+S

	Size	PR	Loading Index	Speed Rating	Tread Depth (mm)	Inflatable Section Width(mm)	Standard Rim	Overall Diameter (mm)	UTQG	MAX Load		MAX Pressure		Sidewall Description
										Kg	lbs	Kpa	Psi	
22	37×12.50R22LT	10PR	123	Q	14.2	318	10J	928	-	1550	3415	450	65	BSW
	35×12.50R22LT	10PR	117	Q	14.2	318	10J	877	-	1285	2835	450	65	BSW
20	35×12.50R20LT	10PR	121	Q	14	318	10J	877	-	1450	3195	450	65	BSW
	33×12.50R20LT	10PR	114	Q	14	318	10J	826	-	1180	2600	450	65	BSW

The labeling information is subject to change without notice.



BRAKING



4 SEASON




STABILITY



DRAINAGE



Off-Road Maximum Traction Tyre, designed for extreme 4X4 application, confidence in performance on muddy, snowy and rocky terrain as well as sealed road performance, with extra ground clearance, higher load-carrying capacity, and greater ability to go off-road. 4X4 enthusiasts know it for its long wear, low noise and aggressive tread pattern.



Strategically placed ribs within the lateral grooves of the tread design help to discharge stones and resist stone drilling.



Specially developed tread compound helps resist the cutting, tearing and chunking commonly developed in extended off-road applications.



Strategically placed in the lower side wall area, a raised rim protector helps protect the wheel and tyre from hazards in off-road driving conditions.

