

07



# S205

Position: ALL Position



- ✔ Premium five-rib tread with various micro sipes to provide high mileage, even wear, low noise.
- ✔ Wide, flat tread optimizes footprint shape for improved handling and response in long haul service.
- ✔ Latest technology carcass geometry and materials for enhanced damage resistance, durability.

Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W. mm	O.D. mm	T.D. mm
	inch				Single	Dual			
11R22.5	8.25	18	S205	149/146M	3250	3000	268	1040	13
12R22.5	9.00	18	S205	152/149M	3550	3250	300	1075	14.5
255/70R22.5	7.50	16	S205	140/137M	2500	2300	254	926	11
295/75R22.5	9.00	16	S205	146/143M	3000	2725	298	1011	11
295/80R22.5	9.00	18	S205	152/149M	3550	3250	292	1044	14.5
315/80R22.5	9.00	20	S205	156/150M	4000	3350	312	1076	14.5
11R24.5	8.25	16	S205	149/146M	3250	3000	279	1104	11
285/75R24.5	8.25	16	S205	147/144M	3075	2800	283	1050	11

UM

445/45R19.5    15.00    24    K    164K    5000    5000    394    5000    15