



# S600

Position: ALL position



- ✔ Latest technology carcass geometry and materials for enhanced damage resistance, durability and loading capacity.
- ✔ Premium Zigzag design promotes soft soil mobility.
- ✔ Offset block shoulder design with SILICA compound promotes good traction and abrasion resistance.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W. mm	O.D. mm	T.D. mm
	inch				Single	Dual			
7.00R16LT	5.50F	14	S600	118/114L	1320	1180	202	768	11
7.50R16	6.00G	14	S600	122/118L	1500	1320	215	800	13
8.25R16	6.50H	16	S600	128/124K	1800	1600	225	848	11.5
8.25R20	6.50	16	S600	139/137K	2430	2300	234	970	15
9.00R20	7.00	16	S600	144/142K	2800	2650	260	1018	15.5
10.00R20	7.50	18	S600	149/146K	3250	3000	278	1051	16.5
11.00R20	8.00	18	S600	152/149K	3550	3250	288	1079	16
12.00R20	8.50	20	S600	156/153K	4000	3650	309	1115	16.3
11R22.5	8.25	16	S600	148/145M	3150	2900	268	1054	14.5
							268		
12R22.5	9.00	18	S600	152/149M	3550	3250	300	1075	14.5
13R22.5	9.75	20	S600	156/150L	4000	3350	320	1124	15.5
11R24.5	8.25	16	S600	149/146M	3250	3000	279	1104	14.5
12.00R24	8.50	20	S600	160/157K	4500	4125	315	1226	16
315/80R22.5	9.00	20	S600	156/150M	4000	3350	312	1076	14.5
295/80R22.5	9.00	18	S600	152/149M	3550	3250	292	1044	15.5