



TR666



Mileage



Safety



Wear

FEATURE:

- Four zigzag grooves design
- Closed shoulder ribs

BENEFIT:

- Good wet and dry traction
- Long life and mileage

ADVANTAGE:

- Good traction
- Scrub resistance in cornering

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs		IP		OTD mm
								Single	Dual	kPa	psi	
7.00R20	126/124L	14	5.50	6.00,6.00S	200	904	422	1700 3750	1600 3520	830	120	13.0
7.50R20	130/128L	14	6.00	6.50,6.50T	215	935	435	1900 4190	1800 3970	830	120	13.0
10.00R20	146/143L	16	7.50	7.50V,8.00	278	1054	486	3000 6610	2725 6005	830	120	15.0
10.00R20	149/146K	18	7.50	7.50V,8.00	278	1054	486	3250 7160	3000 6610	930	135	15.0
11.00R20	150/147K	16	8.00	8.50,8.00V	293	1085	499	3350 7390	3075 6780	830	120	16.0
11.00R20	152/149K	18	8.00	8.50,8.00V	293	1085	499	3550 7830	3250 7160	930	135	16.0
12.00R20	154/151K	18	8.50	8.50V,9.00	315	1125	516	3750 8270	3450 7610	830	120	16.5
12.00R20	156/153K	20	8.50	8.50V,9.00	315	1125	516	4000 8820	3650 8050	900	131	16.5
8R22.5	130/128M	14	6.00	5.25,6.75	203	935	440	1900 4190	1800 3970	830	120	13.0
11R22.5	144/142M	14	8.25	7.50	279	1054	491	2800 6175	2650 5840	720	105	15.0
11R22.5	146/143M	16	8.25	7.50	279	1054	491	3000 6610	2725 6005	830	120	15.0
11R22.5	148/144M	16+	8.25	7.50	279	1054	491	6610	5800	Single:120 Dual:110		15.0
11R22.5	148/144M	18	8.25	7.50	279	1054	491	3150 6940	2800 6175	930	135	15.0
11R22.5	149/146M	18	8.25	7.50	279	1054	491	3250 7160	3000 6610	930	135	15.0
12R22.5	143/141L	12	9.00	8.25	300	1085	504	2725 6005	2575 5675	620	90	15.0
12R22.5	143/141L	12+	9.00	8.25	300	1085	504	2725 6005	2575 5675	620	90	15.0
12R22.5	150/147L	16	9.00	8.25	300	1085	504	3350 7390	3075 6780	830	120	15.0
12R22.5	152/148L	16	9.00	8.25	300	1085	504	3550 7825	3150 6945	900	130	15.0
12R22.5	152/149K	18	9.00	8.25	300	1085	504	3550 7830	3250 7160	930	135	15.0
275/80R22.5	149/146M	16	8.25	7.50	276	1012	473	3250 7165	3000 6615	850	125	14.0
315/80R22.5	154/151M	18	9.00	9.75	312	1076	500	3750 8270	3450 7610	830	120	15.0
315/80R22.5	157/154L	20	9.00	9.75	312	1076	500	4125 9090	3750 8270	900	130	15.0
295/75R22.5	144/141M	14	9.00	8.25	298	1014	474	2800 6175	2575 5675	760	110	15.0
295/75R22.5	146/143M	16	9.00	8.25	298	1014	474	3000 6610	2725 6005	830	120	15.0

TR666JS

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs		IP		OTD mm
								Single	Dual	kPa	psi	
9.00R20	141/139K	14	7.0	7.00T,7.5	259	1019	471	2575 5675	2430 5355	790	115	16.0
9.00R20	144/142K	16	7.0	7.00T,7.5	259	1019	471	2800 6175	2650 5840	900	130	16.0
10.00R20	146/143K	16	7.5	7.50V,8.0	278	1054	486	3000 6610	2725 6005	830	120	17.0
10.00R20	149/146K	18	7.5	7.50V,8.0	278	1054	486	3250 7160	3000 6610	930	135	17.0
11.00R20	150/147K	16	8.0	8.5,8.00V	293	1085	499	3350 7390	3075 6780	830	120	18.0
11.00R20	152/149K	18	8.0	8.5,8.00V	293	1085	499	3550 7830	3250 7160	930	135	18.0
12.00R20	154/151K	18	8.5	8.50V,9.0	315	1125	516	3750 8270	3450 7610	830	120	19.0

• TR666-JS is the derived, deeper OTD pattern on TR666