



TR668



Mileage



Safety



Wear

FEATURE:

- Classic mixed pattern designed for regional-mixed operation
- Enhanced casing package

Benefit:

- Good mileage and traction
- Good retreadability

ADVANTAGE:

- An all round pattern with wear performance and traction
- Increased casing toughness

TR668

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs		IP		OTD mm
								Single	Dual	kPa	psi	
7.50R15TR	136/134J	18	6.00	5.50,6.50	215	808	372	2240 4940	2120 4675	830	120	12.5
7.50R16LT	105/101L	6	6.00G	5.50F,6.50H	215	805	375	925 2040	825 1820	350	50	12.5
7.50R16LT	112/107L	8	6.00G	5.50F,6.50H	215	805	375	1120 2470	975 2150	460	65	12.5
7.50R16LT	122/118L	14	6.00G	5.50F,6.50H	215	805	375	1500 3305	1320 2910	770	110	12.5
7.50R16LT	125/121L	16	6.00G	5.50F,6.50H	215	805	375	1650 3640	1450 3195	870	126	12.5
8.25R16LT	110/105M	6	6.50H	6.00G,6.50	235	855	397	1060 2335	925 2040	320	45	13.0
8.25R16LT	126/122M	14	6.50H	6.00G,6.50	235	855	397	1700 3750	1500 3305	670	97	13.0
8.25R16LT	128/124M	16	6.50H	6.00G,6.50	235	855	397	1800 3970	1600 3525	770	112	13.0
8.25R16LT	132/128L	18	6.50H	6.00G,6.50	235	855	397	2000 4410	1800 3970	870	126	13.0
8.25R20	136/134L	14	6.50	6.50T,7.00,7.00T	236	974	452	2240 4940	2120 4675	830	120	14.0
8.25R20	139/137L	16	6.50	6.50T,7.00,7.00T	236	974	452	2430 5355	2300 5070	930	135	14.0
9.00R20	141/139L	14	7.00	7.00T,7.50	259	1019	471	2575 5675	2430 5355	790	115	15.5
9.00R20	141/139K	14	7.00	7.00T,7.50	259	1019	471	2575 5675	2430 5355	790	115	15.5
9.00R20	144/142K	16	7.00	7.00T,7.50	259	1019	471	2800 6175	2650 5840	900	130	15.5
9.00R20	144/142L	16	7.00	7.00T,7.50	259	1019	471	2800 6175	2650 5840	900	130	15.5
10.00R20	146/143K	16	7.50	7.50V,8.00	278	1054	486	3000 6610	2725 6005	830	120	16.5
10.00R20	146/143L	16	7.50	7.50V,8.00	278	1054	486	3000 6610	2725 6005	830	120	16.5
10.00R20	149/146K	18	7.50	7.50V,8.00	278	1054	486	3250 7160	3000 6610	930	135	16.5
10.00R20	149/146L	18	7.50	7.50V,8.00	278	1054	486	3250 7160	3000 6610	930	135	16.5
11.00R20	143/141K	12	8.00	8.50,8.00V	293	1085	499	2725 6005	2575 5675	620	90	17.0
11.00R20	150/147K	16	8.00	8.50,8.00V	293	1085	499	3350 7390	3075 6780	830	120	17.0
11.00R20	150/147L	16	8.00	8.50,8.00V	293	1085	499	3350 7390	3075 6780	830	120	17.0
11.00R20	152/149K	18	8.00	8.50,8.00V	293	1085	499	3550 7830	3250 7160	930	135	17.0
11.00R20	152/149L	18	8.00	8.50,8.00V	293	1085	499	3550 7830	3250 7160	930	135	17.0
12.00R20	152/149K	16	8.50	8.50V,9.00	315	1125	516	3550 7830	3250 7160	760	110	17.5
12.00R20	154/151K	18	8.50	8.50V,9.00	315	1125	516	3750 8270	3450 7610	830	120	17.5
12.00R20	154/151L	18	8.50	8.50V,9.00	315	1125	516	3750 8270	3450 7610	830	120	17.5
12.00R20	154/151K	18	8.50	8.50V,9.00	315	1125	516	3730 8210	3270 7200	840	120	17.5
12.00R20	156/153K	20	8.50	8.50V,9.00	315	1125	516	4000 8820	3650 8050	900	131	17.5
12.00R20	158/155J	22	8.50	8.50V,9.00	315	1125	516	4250 9370	3875 8540	970	141	17.5
12.00R20	158/155J	22	8.50	8.50V,9.00	315	1125	516	4250 9370	3875 8540	970	141	17.5
9R22.5	136/134L	14	6.75	6.00,7.50	229	974	457	2240 4940	2120 4675	830	120	14.0
11R22.5	144/142M	14	8.25	7.50	279	1054	491	2800 6175	2650 5840	720	105	16.5
11R22.5	146/143M	16	8.25	7.50	279	1054	491	3000 6610	2725 6005	830	120	16.5
11R22.5	148/145L	16+	8.25	7.50	279	1054	491	3150 6940	2900 6395	850	125	16.5
12R22.5	143/141L	12	9.00	8.25	300	1085	504	2725 6005	2575 5675	620	90	17.0
12R22.5	150/147L	16	9.00	8.25	300	1085	504	3350 7390	3075 6780	830	120	17.0
12R22.5	152/149K	18	9.00	8.25	300	1085	504	3550 7830	3250 7160	930	135	17.0
13R22.5	156/153L	18	9.75	9.00	320	1124	521	4000 8820	3650 8050	875	127	17.5
13R22.5	156/153L	20	9.75	9.00	320	1124	521	4000 8820	3650 8050	930	135	17.5
11R24.5	146/143M	14	8.25	7.50	279	1104	516	3000 6610	2725 6005	720	105	16.5
11R24.5	149/146M	16	8.25	7.50	279	1104	516	3250 7160	3000 6610	830	120	16.5
295/80R22.5	152/148L	16	9.00	8.25	298	1044	487	3550 7825	3150 6945	850	125	17.5
295/80R22.5	152/149L	18	9.00	8.25	298	1044	487	3550 7825	3250 7160	900	130	17.5
315/80R22.5	154/151M	18	9.00	9.75	312	1076	500	3750 8270	3450 7610	830	120	17.5
315/80R22.5	157/154L	20	9.00	9.75	312	1076	500	4125 9090	3750 8270	900	130	17.5
315/80R22.5	161/157K	20	9.00	9.75	312	1076	500	4625 10200	4125 9090	900	130	17.5

• LT sizes available

TR668A

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs				IP		OTD mm
								Single		Dual		kPa	psi	
7.00R16LT	101/96M	6	5.50F	6.00G	200	775	362	825	1820	710	1565	350	50	11.5
7.00R16LT	107/102L	8	5.50F	6.00G	200	775	362	975	2150	850	1875	460	67	11.5
7.00R16LT	115/111M	12	5.50F	6.00G	200	775	362	1220	2690	1075	2370	670	97	11.5
7.00R16LT	118/114L	14	5.50F	6.00G	200	775	362	1320	2910	1180	2600	770	112	11.5
9.00R16LT	131/126L	14	6.50H	6.00G,6.50	255	890	416	1950	4300	1700	3750	670	97	14.0
9.00R16LT	134/129K	16	6.50H	6.00G,6.50	255	890	416	2120	4680	1850	4080	770	112	14.0

• TR668A is the derived pattern on TR668 for sizes 7.00R16 and 9.00R16

TR668-I

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs				IP		OTD mm
								Single		Dual		kPa	psi	
9.00R20	141/139L	14	7.00	7.00T,7.50	259	1019	471	2575	5675	2430	5355	790	115	15.5
9.00R20	144/142L	16	7.00	7.00T,7.50	259	1019	471	2800	6175	2650	5840	900	130	15.5
10.00R20	146/143L	16	7.50	7.50V,8.00	278	1054	486	3000	6610	2725	6005	830	120	15.0
10.00R20	149/146L	18	7.50	7.50V,8.00	278	1054	486	3250	7160	3000	6610	930	135	15.0
11.00R20	143/141L	12+	8.00	8.50,8.00V	293	1085	499	2725	6005	2575	5675	620	90	15.0
11.00R20	150/147L	16	8.00	8.50,8.00V	293	1085	499	3350	7390	3075	6780	830	120	15.0
11.00R20	152/149K	18	8.00	8.50,8.00V	293	1085	499	3550	7830	3250	7160	930	135	15.0
12.00R20	154/151L	18	8.50	8.50V,9.00	315	1125	516	3750	8270	3450	7610	830	120	16.0
11R22.5	144/142L	14	8.25	7.50	279	1054	491	2800	6175	2650	5840	720	105	15.0
11R22.5	146/143L	16	8.25	7.50	279	1054	491	3000	6610	2725	6005	830	120	15.0
12R22.5	143/141L	12	9.00	8.25	300	1085	504	2725	6005	2575	5675	620	90	15.0
12R22.5	143/141L	12+	9.00	8.25	300	1085	504	2725	6005	2575	5675	620	90	15.0
12R22.5	150/147L	16	9.00	8.25	300	1085	504	3350	7390	3075	6780	830	120	15.0
12R22.5	152/149K	18	9.00	8.25	300	1085	504	3550	7830	3250	7160	930	135	15.0

• TR668-I is the derived pattern on TR668 for Trailer OE