



TR688



Mileage



Safety



Wear

FEATURE:

- Center rib plus open shoulder design
- Deep OTD
- Strong casing package

ADVANTAGE:

- Provides good traction in wet/dry conditions
- Long tread wear life
- Increased casing toughness

BENEFIT:

- Good traction for handling
- Good mileage
- Improved retreadability

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs				IP		OTD mm
								Single		Dual		kPa	psi	
9.00R20	141/139L	14	7.00	7.00T,7.50	259	1019	471	2575	5675	2430	5355	790	115	16.0
9.00R20	144/142K	16	7.00	7.00T,7.50	259	1019	471	2800	6175	2650	5840	900	130	16.0
11R22.5	144/142M	14	8.25	7.50	279	1054	491	2800	6175	2650	5840	720	105	18.0
11R22.5	146/143M	16	8.25	7.50	279	1054	491	3000	6610	2725	6005	830	120	18.0
11R22.5	148/144M	16+	8.25	7.50	279	1054	491		6610		5800	Single: 120 Dual: 110		18.0
12R22.5	150/147L	16	9.00	8.25	300	1085	504	3350	7390	3075	6780	830	120	20.0
12R22.5	152/149K	18	9.00	8.25	300	1085	504	3550	7830	3250	7160	930	135	20.0
11R24.5	146/143M	14	8.25	7.50	279	1104	516	3000	6610	2725	6005	720	105	18.0
11R24.5	149/146M	16	8.25	7.50	279	1104	516	3250	7160	3000	6610	830	120	18.0
295/80R22.5	152/148M	16	9.00	8.25	298	1044	487	3550	7825	3150	6945	850	125	18.0
295/80R22.5	152/149L	18	9.00	8.25	298	1044	487	3550	7825	3250	7160	900	130	18.0
315/80R22.5	151/148M	16	9.00	9.75	312	1076	500	3450	7610	3150	6940	760	110	20.0
315/80R22.5	154/151M	18	9.00	9.75	312	1076	500	3750	8270	3450	7610	830	120	20.0
315/80R22.5	157/154L	20	9.00	9.75	312	1076	500	4125	9090	3750	8270	900	130	20.0
295/75R22.5	144/141M	14	9.00	8.25	298	1014	474	2800	6175	2575	5675	760	110	18.0
295/75R22.5	146/143M	16	9.00	8.25	298	1014	474	3000	6610	2725	6005	830	120	18.0