



**SUNFULL
TIRES**

Truck and Bus Tire Catalog

**SUNFULL
TIRES**

Shandong Changfeng Tyres Co., Ltd.

Dawang Economic Development Zone, Dongying, Shandong, 257335, China

Tel: +86 546 6893270 Fax: +86 546 6893669

Website: <http://www.changfengtires.com>

E-mail: sales@changfengtires.com





Shandong Changfeng Tyres Co., Ltd.

Company Profile:

SUNFULLTires, enjoying high popularity in both domestic and international markets, is one of the major brands developed by Shandong Changfeng Tyres Co., Ltd.

Shandong Changfeng Tyres Co., Ltd., one of the major tire manufacturers in China, was established in 1995 and covers an area of 2 million square meters, with total assets of over 5 billion RMB and more than 10,000 employees. The company owns 6 plants in Dongying and Linyi city, Shandong province, China. Three plants are for TBR products with annual production capacity of 6 million tires, another three plants are for PCR products with annual production capacity of 30 million tires.

Changfeng specializes in manufacturing radial tires which are widely used in passenger car, SUV, light truck, truck and bus etc., and in all seasons with excellent performance, which are well-reputed all over the world.

Changfeng takes pride in its experienced R&D team and advanced testing facilities, which assure the excellent and stable quality of its products. Many of Changfeng's manufacturing equipments are imported from Europe, United States and Japan.

Changfeng has built a strong quality assurance system and its products are accredited with certificates of ISO9001, IATF16949, DOT, ECE, GCC, INMETRO, CCC, BIS, SNI, SONCAP, etc.



We export to more than 120 countries in the world


SUNFULL
RADIAL
PRTTERN
RANGE

POSITION

ALL POSITION



STEER/TRAILER



DRIVE



TRAILER



LONG & REGIONAL HAUL



MIXED SERVICE



OFF ROAD





ALL POSITION



HF708

Features

- Three groove design with lugs
- Special tread compound
- Shoulder design with lugs and sipes

Benefits

- Provide outstanding wet performance
- Provide outstanding resistance to abrasion
- Provide excellent heat dissipation



HF117

Features

- Three zigzag grooves design with lugs
- Special tread compound
- Shoulder design with lugs and sipes

Benefits

- Provide excellent wet performance
- Provide outstanding resistance to abrasion
- Provide outstanding heat dissipation



HF599+

Features

- Four circumferential grooves
- Ladder arrangement design of longitudinal pattern
- Special tread compound
- Reinforced carcass and bead design

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Reduce irregular wear greatly
- Provide outstanding resistance to abrasion
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF599

Features

- Four circumferential grooves
- Ladder arrangement design of longitudinal pattern
- Special tread compound
- Reinforced carcass and bead design

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Reduce irregular wear greatly
- Provide outstanding resistance to abrasion
- Ensure excellent handling and safe performance and provide outstanding loading capacity



Long Haul



Regional Haul



Operation:

- Highways and long distance / Regional highways and city streets
- Well paved road conditions / Mainly used on paved roads, occasionally run on unpaved roads
- Constant and high speed with minimal braking and accelerating / Frequent braking, accelerating and turning

Size	HF708	HF117	HF599+	HF599
7.50R16				125/121 L
9.00R20	144/142 K			
10.00R20	149/146 K			
11.00R20	152/149 K			
12.00R20	156/153 K			
12.00R24	160/157 K			
12R22.5		152/149 L		
			152/149 J	152/149 K



STEER/TRAILER



Features

- Four wide circumferential grooves
- Special groove design
- Siped rib and shoulder design

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Deliver stone-ejecting property
- Provide excellent heat dissipation

***HF330**



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance

***HF660**



Features

- Four zigzag grooves
- Solid shoulder design
- Variable pitch design
- Specially designed compound

Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Provide outstanding resistance to abrasion
- Reduce rolling noise greatly
- Deliver lower rolling resistance

***HF606**



Features

- Four zigzag grooves
- Solid shoulder design
- Variable pitch design
- Specially designed compound

Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Provide outstanding resistance to abrasion
- Reduce rolling noise greatly
- Deliver lower rolling resistance

***HF606+**

Size	HF330	HF660	HF606	HF606+	Remarks
9.00R20			144/142 K		The symbol of "*" represents patterns applicable for all position bus.
10.00R20			149/146 K		
11.00R20			152/149 K		
12.00R20			156/153 K		
11R22.5	148/145 M	148/145 M	148/145 M		
12R22.5	152/149 M	152/149 M			
13R22.5		156/152 L(154/151 M)			
215/75R17.5		135/133 J			
255/70R22.5		140/137 L			
295/80R22.5		152/149 M			
315/70R22.5		154/150 L(152/148 M)			
315/80R22.5		156/152 L(154/151 M)		156/152 L(154/151 M)	



STEER/TRAILER



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Deliver lower rolling resistance

HF688



Features

- Solid rib design combined with multiple sipes
- Four wide circumferential grooves
- Solid shoulder design

Benefits

- Provide excellent heat dissipation and improved regular wear with lower resistance
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide outstanding resistance to abrasion

HF111



Features

- Four circumferential grooves
- Solid shoulder design
- Specially designed compound

Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Provide outstanding resistance to abrasion
- Reduce rolling noise greatly
- Deliver lower rolling resistance

HF121



Features

- Four circumferential grooves
- Solid shoulder design
- Specially designed compound

Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Provide outstanding resistance to abrasion
- Reduce rolling noise greatly
- Deliver lower rolling resistance

HF123

Size	HF688	HF111	HF121	HF123
8.25R16			128/124 M	
9.5R17.5			143/141 J	
11.00R20			152/149 K	152/149 K
11R22.5		146/143 L		
11R24.5		146/143 M		
11R24.5		149/146 L		
215/75R17.5		135/133 J		
235/75R17.5		143/141 J		
225/70R19.5		128/126 L		
245/70R19.5		135/133 L		
255/70R22.5		140/137 L		
295/75R22.5		144/141 M		
295/75R22.5		146/143 L		
295/80R22.5	152/149 M		152/149 M	
315/70R22.5			154/150 L(152/148 M)	
315/80R22.5			156/152 L(154/151 M)	
285/75R24.5		144/141 M		
285/75R24.5		147/144 L		



STEER/TRAILER



HF124

Features

- Solid rib design combined with multiple sipes
- Four wide circumferential grooves
- Solid shoulder design

Benefits

- Provide excellent heat dissipation and improved regular wear with lower resistance
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide outstanding resistance to abrasion



HF680

Features

- Solid rib design combined with multiple sipes
- Four wide circumferential grooves
- Solid shoulder design

Benefits

- Provide excellent heat dissipation and improved regular wear with lower resistance
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide outstanding resistance to abrasion



HF127

Features

- Solid rib design combined with multiple sipes
- Four wide circumferential grooves
- Solid shoulder design

Benefits

- Provide excellent heat dissipation and improved regular wear with lower resistance
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide outstanding resistance to abrasion



HF788

Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance

Size	HF124	HF680	HF127	HF788
7.50R16LT			125/121 L	
295/80R22.5				152/149 M
315/80R22.5	156/152 L(154/151 M)	156/152 L(154/151 M)		



STEER/TRAILER



HF689

Features

- Solid rib design combined with multiple sipes
- Four wide circumferential grooves
- Solid shoulder design

Benefits

- Provide excellent heat dissipation and improved regular wear with lower resistance
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide outstanding resistance to abrasion



HF061

Features

- Optimized ratio of tread block
- Specific tread compound formula for regional and long haul application
- Deepen the pattern grooves and widen tire crown design
- 4 circumferential groove design

Benefits

- Excellent grounding contact shape for improved wear performance Provide good wear life
- Effectively improve the handling stability and wear resistance
- Optimize tire shoulder design to improve crown burst performance
- Reduce rolling resistance, provide good straight-line driving performance

Size	HF689	HF061
12.00R24	160/157 K	
12R22.5		152/149 L



STEER/TRAILER



HF976

Features

- Optimized ratio of tread block
- Specific tread compound formula for regional and long haul application
- Stone rejectors in grooves
- 3 tortuous longitudinal groove design

Benefits

- Improve uneven wear
- Provide good wear life
- Provide resistance to stone drilling and protecting the bottom of the grooves
- All position with strong applicability



HF979

Features

- Stone rejectors in grooves
- Wide tire shoulder
- Straight narrow grooves design
- Wide longitudinal groove pattern design

Benefits

- Provide resistance to stone drilling to avoid grooves cracks
- Improve uneven wear
- Provide excellent water drainage performance
- Provide good water drainage performance and stable handling on wet road



HF192

Features

- Optimized ratio of tread block
- Specific tread compound formula for regional and long haul application
- Deepen the pattern grooves and widen tire crown design
- 4 circumferential groove design

Benefits

- Excellent grounding contact shape for improved wear performance Provide good wear life
- Effectively improve the handling stability and wear resistance
- Optimize tire shoulder design to improve crown burst performance
- Reduce rolling resistance, provide good straight-line driving performance

Size

HF976

152/149 L

HF979

152/149 L

HF192

152/149 L

12R22.5



STEER/TRAILER



HF571

Features

- Optimized ratio of tread block
- Specific tread compound formula for regional and long haul application
- Stone rejectors in grooves
- 3 tortuous longitudinal groove design

Benefits

- Improve uneven wear
- Provide good wear life
- Provide resistance to stone drilling and protecting the bottom of the grooves
- All position with strong applicability



HF661

Features

- Stone rejectors in grooves
- Wide tire shoulder
- Straight narrow grooves design
- Wide longitudinal groove pattern design

Benefits

- Provide resistance to stone drilling to avoid grooves cracks
- Improve uneven wear
- Provide excellent water drainage performance
- Provide good water drainage performance and stable handling on wet road



HF685

Features

- Stone rejectors in grooves
- Wide tire shoulder
- Straight narrow grooves design
- Wide longitudinal groove pattern design

Benefits

- Provide resistance to stone drilling to avoid grooves cracks
- Improve uneven wear
- Provide excellent water drainage performance
- Provide good water drainage performance and stable handling on wet road

Size

HF571

152/149 L

HF661

152/149 L

HF685

152/149 M

12R22.5
295/80R22.5



DRIVE



HF122

Features

- Three circumferential grooves
- Block pattern design
- Special tread compound
- Solid shoulder design

Benefits

- Ensure outstanding water evacuation, even pressure distribution and heat dissipation
- Provide excellent driving and braking force
- Provide outstanding resistance to puncture and tearing
- Provide outstanding resistance to abrasion



HF668

Features

- Special tread compound
- Four circumferential grooves
- Deeper tread depth design
- Block pattern design

Benefits

- Provide outstanding resistance to puncture and tearing
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Improved mileage performance
- Provide excellent driving and braking force



HF628

Features

- Asymmetric lug design
- Block pattern design
- Four circumferential grooves
- Reinforced carcass and bead design

Benefits

- Combine regular wear with excellent traction
- Provide excellent driving and braking force
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF607

Features

- Four circumferential grooves
- Block pattern design
- Special tread compound
- Solid shoulder design

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent driving and braking force
- Provide outstanding resistance to puncture and tearing
- Provide outstanding resistance to abrasion

Size	HF122	HF668	HF628	HF607
10.00R20		149/146 K		
12.00R24	160/157 K			160/157 K
11R22.5			148/145 M	
12R22.5			152/149 M	
13R22.5			156/152 L(154/151 M)	
215/75R17.5			135/133 J	
235/75R17.5			143/141 J	
295/80R22.5		152/149 M	152/149 M	
315/70R22.5			154/150 L(152/148 M)	
315/80R22.5	156/152 L(154/151 M)		156/152 L(154/151 M)	



DRIVE



HF312

Features

- Block pattern design
- Solid shoulder design
- Four wide circumferential grooves

Benefits

- Provide excellent driving and braking force
- Provide outstanding resistance to abrasion
- Ensure excellent water evacuation, even pressure distribution and heat dissipation



HF638

Features

- Block pattern design
- Extra wide footprint
- Deeper tread depth design

Benefits

- Provide excellent driving and braking force
- Enhanced stability and resistance to abrasion
- Improved mileage performance



HF505

Features

- Block pattern design
- Extra wide footprint
- Deeper tread depth design

Benefits

- Provide excellent driving and braking force
- Enhanced stability and resistance to abrasion
- Improved mileage performance



HF323

Features

- Block pattern design
- Open shoulder design
- Special tread compound

Benefits

- Provide excellent traction
- Improved heat dissipation to increase tire life
- Provide mileage performance

Size	HF312	HF638	HF505	HF323
9.00R20		144/142 K		
10.00R20		149/146 K	149/146 D	
11R22.5	146/143 L	148/145 M		146/143 L
12R22.5	152/149 M			
11R24.5	146/143 M			146/143 M
11R24.5	149/146 L			149/146 L
295/75R22.5	144/141 M			144/141 M
295/75R22.5	146/143 L			146/143 L
315/70R22.5		154/150 L(152/148 M)		
315/80R22.5		156/152 L(154/151 M)		
285/75R24.5	144/141 M			144/141 M
285/75R24.5	147/144 L			147/144 L



DRIVE



HF326

Features

- Asymmetric lug design
- Block pattern design
- Four circumferential grooves
- Reinforced carcass and bead design

Benefits

- Combine regular wear with excellent traction
- Provide excellent driving and braking force
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF328

Features

- Block pattern design
- Extra wide footprint
- Deeper tread depth design

Benefits

- Provide excellent driving and braking force
- Enhanced stability and resistance to abrasion
- Improved mileage performance



HF331

Features

- Block pattern design
- Solid shoulder design
- Four wide circumferential grooves

Benefits

- Provide excellent driving and braking force
- Provide outstanding resistance to abrasion
- Ensure excellent water evacuation, even pressure distribution and heat dissipation



HF616

Features

- Asymmetric lug design
- Block pattern design
- Four circumferential grooves
- Reinforced carcass and bead design

Benefits

- Combine regular wear with excellent traction
- Provide excellent driving and braking force
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Ensure excellent handling and safe performance and provide outstanding loading capacity

Size	HF326	HF328	HF331	HF616
9.00R20				144/142 K
10.00R20				149/146 K
12.00R20				156/153 K
295/80R22.5	152/149 M			
315/70R22.5	154/150 L(152/148 M)			
315/80R22.5	156/152 L(154/151 M)	156/152 L(154/151 M)	156/152 L(154/151 M)	



DRIVE



HF626

Features

- Block pattern design
- Solid shoulder design
- Four wide circumferential grooves

Benefits

- Provide excellent driving and braking force
- Provide outstanding resistance to abrasion
- Ensure excellent water evacuation, even pressure distribution and heat dissipation



HF327

Features

- Block pattern design
- Solid shoulder design
- Four wide circumferential grooves

Benefits

- Provide excellent driving and braking force
- Provide outstanding resistance to abrasion
- Ensure excellent water evacuation, even pressure distribution and heat dissipation

Size	HF626	HF638+	HF327
10.00R20	149/146 K		
12R22.5		152/149 M	
315/80R22.5			156/152 L(154/151 M)



DRIVE



HF051

Features

- Asymmetric lug design
- Block pattern design
- Four circumferential grooves
- Reinforced carcass and bead design

Benefits

- Combine regular wear with excellent traction
- Provide excellent driving and braking force
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF081

Features

- Optimized ratio of tread block
- Deepened pattern groove, Specific tread compound formula for regional and long haul application
- Multiple angle groove wall design
- 4-ply belt design
- 3 tortuous longitudinal groove design

Benefits

- Shape for improved wear performance
- Provide good wear life
- Good self-cleaning performance, protecting the bottom of the grooves
- Promote uniform wear
- All position with strong applicability



HF565

Features

- Optimized ratio of tread block
- Deepened pattern groove, Specific tread compound formula for regional and long haul application
- Multiple angle groove wall design
- 4-ply belt design
- 3 tortuous longitudinal groove design

Benefits

- Shape for improved wear performance
- Provide good wear life
- Good self-cleaning performance, protecting the bottom of the grooves
- Promote uniform wear
- All position with strong applicability

Size	HF051	HF081	HF565
12R22.5	152/149 K	152/149 L	152/149 L



HF391

Features

- Special tread compound
- Lug and special block pattern design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance



HF533

Features

- Block pattern design
- Extra wide footprint
- Deeper tread depth design

Benefits

- Provide excellent driving and braking force
- Enhanced stability and resistance to abrasion
- Improved mileage performance



HF538

Features

- Block pattern design
- Extra wide footprint
- Deeper tread depth design

Benefits

- Provide excellent driving and braking force
- Enhanced stability and resistance to abrasion
- Improved mileage performance



HF806

Features

- Block pattern design
- Solid shoulder design
- Four wide circumferential grooves

Benefits

- Provide excellent driving and braking force
- Provide outstanding resistance to abrasion
- Ensure excellent water evacuation, even pressure distribution and heat dissipation

Size	HF391	HF533	HF538	HF806
12.00R20	156/153 J			
295/80R22.5		152/149 M	152/149 M	152/149 M
315/70R22.5		156/150L(154/150M)	156/150L(154/150M)	
315/80R22.5		156/152L(154/151M)		



TRAILER



Features

- Four zigzag grooves
- Extra wide footprint with square shoulder
- Special tread compound

Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Enhanced stability and resistance to abrasion
- Provide outstanding resistance to abrasion



Features

- Four circumferential grooves
- Special groove design
- Curved lug design

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Deliver stone-ejecting property
- Deliver excellent driving and braking force



Features

- Four circumferential groove designs
- Reduced tire weight

Benefits

- Improved antiskid performance
- Deliver rolling resistance and lower fuel consumption



Features

- Four zigzag grooves
- Extra wide footprint with square shoulder
- Special tread compound

Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Enhanced stability and resistance to abrasion
- Provide outstanding resistance to abrasion

Size	ST022	HF618	HF126	ST026
11R22.5		148/145 M	146/143 L	148/145 M
12R22.5		152/149 M		
11R24.5			149/146 L	
235/75R17.5	143/141 J			
295/75R22.5		144/141 M		
295/75R22.5		146/143 L	146/143 L	
295/80R22.5				152/149 M
315/70R22.5				156/150L(154/150M)
315/80R22.5				156/152L(154/151M)
385/55R22.5				164 K
385/65R22.5	160 K			164 K
285/75R24.5			147/144 L	



Mixed
Service



Operation:

- Frequently used on and off roads
- Heavier loads
- Construction site



ALL POSITION


HF702

Features

- Three zigzag grooves
- Combination of rib and lug design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation


ST011

Features

- Three zigzag grooves
- Combination of rib and lug design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation


HF307

Features

- Three zigzag grooves
- Reinforced carcass and bead design
- Special groove design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Ensure excellent handling and safe performance and provide outstanding loading capacity
- Deliver stone-ejecting property
- Provide excellent heat dissipation


HF708+

Features

- Three zigzag grooves
- Combination of rib and lug design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation

Size	HF702	ST011	HF307	HF708+
6.50R16LT	110/105 K			
7.00R16LT	118/114 M			
7.50R16LT	122/118 M			
8.25R16LT	128/124 M			
8.25R20	139/137 L			
9.00R20	144/142 K			
10.00R20	149/146 K		149/146 K	
11.00R20	152/149 K		152/149 K	
12.00R20	156/153 K		156/153 K	
12.00R24	160/157 K			
11R22.5	148/145 M			
12R22.5	152/149 M		152/149 L	
13R22.5	156/152 L(154/151 M)			
11R24.5	149/146 L			
315/80R22.5		156/152 L(154/151 M)		156/152 L(154/151 M)



ALL POSITION


RS HF572

Features

- Three zigzag grooves
- Combination of rib and lug design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation


HF573

Features

- Three zigzag grooves
- Combination of rib and lug design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation

Size	RS HF572	HF573
9.5R17.5	143/141 J	
13R22.5		156/153 L
325/95R24	162/160 K	

HF768

Features

- Special tread compound
- Block pattern design
- Extra wide footprint with square shoulder
- Reinforced carcass and bead design

Benefits

- Provide outstanding resistance to puncture and tearing
- Provide excellent driving and braking force
- Enhanced stability and resistance to abrasion
- Ensure excellent handling and safe performance and provide outstanding loading capacity

HF706

Features

- Lug and block pattern design
- Special tread compound

Benefits

- Improved traction, driving and braking performance
- Provide outstanding resistance to puncture and tearing

HF701

Features

- Special tread compound
- Lug and block pattern design
- Siped pattern and shoulder design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance
- Provide excellent heat dissipation

HF313

Features

- Lug and block pattern design
- Special groove design
- Special tread compound
- Open shoulder design

Benefits

- Improved traction, driving and braking performance
- Deliver stone-ejecting property
- Provide outstanding resistance to puncture and tearing
- Provide excellent heat dissipation

Size	HF768	HF706	HF701	HF313
7.00R16LT		118/114 M		
7.50R16LT		122/118 M		122/118 M
8.25R16LT		128/124 M		128/124 M
8.25R20		139/137 L		139/137 K
9.00R20		144/142 K	144/142 K	144/142 K
10.00R20	149/146 D	149/146 K	149/146 K	149/146 K
11.00R20	152/149 J	152/149 K	152/149 K	152/149 K
12.00R20	156/153 J	156/153 K	156/153 K	156/153 K
11R22.5			148/145 L	
12R22.5	152/149 M		152/149 M	
13R22.5	156/152 L(154/151 M)			
295/80R22.5	152/149 K			
315/80R22.5	156/152 L(154/151 M)			

HF322

Features

- Special tread compound
- Lug and special block pattern design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance

HF729

Features

- Special tread compound
- Lug and special block pattern design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance

HF303

Features

- Inter-connected block pattern
- Reinforced carcass and bead design
- Special groove design

Benefits

- Provide excellent driving force, cutting resistance and even wear
- Ensure excellent handling and safe performance and provide outstanding loading capacity
- Deliver stone-ejecting property

HF325

Features

- Special tread compound
- Lug and special block pattern design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance

Size	HF322	HF729	HF303	HF325
7.00R16LT			118/114 K	
7.50R16LT			122/118 J	
8.25R16LT			128/124 J	
8.25R20			139/137 K	
9.00R20			144/142 J	
10.00R20		149/146 K	149/146 J	
11.00R20			152/149 J	
12.00R20			156/153 J	
12.00R24	160/157 K	160/157 K		160/157 K
11R22.5		148/145 L		
315/80R22.5	156/152 L(154/151 M)			

HF768W

Features

- Large block & Deep groove design
- Open shoulder design
- Optimized tread compound
- Special horizontal small groove design

Benefits

- Provides excellent traction and braking force
- Provides good traction and self-cleaning performance
- Provides excellent tear resistance, cut resistance and snow traction
- Improve snow traction performance

HF399

Features

- Special tread compound
- Lug and special block pattern design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance

RsHF373

Features

- Special tread compound
- Lug and special block pattern design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance

Size	HF768W	HF399	RsHF373
9.00R20		144/142 K	
10.00R20		149/146 K	
11.00R20		152/149 K	
12.00R20		156/153 K	
315/80R22.5	156/152 L(154/151 M)		
325/95R24			162/160 K

HF556

Features

- Large block & Deep groove design
- Open shoulder design
- Optimized tread compound
- Special horizontal small groove design

Benefits

- Provides excellent traction and braking force
- Provides good traction and self-cleaning performance
- Provides excellent tear resistance, cut resistance and snow traction
- Improve snow traction performance

HF557

Features

- Large block & Deep groove design
- Open shoulder design
- Optimized tread compound
- Special horizontal small groove design

Benefits

- Provides excellent traction and braking force
- Provides good traction and self-cleaning performance
- Provides excellent tear resistance, cut resistance and snow traction
- Improve snow traction performance

HF335

Features

- Special tread compound
- Lug and block pattern design
- Siped pattern and shoulder design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance
- Provide excellent heat dissipation

HF336

Features

- Special tread compound
- Lug and block pattern design
- Siped pattern and shoulder design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance
- Provide excellent heat dissipation

Size	HF556	HF557	HF335	HF336
9.5R17.5			143/141 J	
13R22.5				156/153 L
295/80R22.5	152/149 M	152/149 M		
315/80R22.5	156/152L(154/151M)	156/152L(154/151M)		



HF168

Features

- Special tread compound
- Lug and special block pattern design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance



HF707

Features

- Special tread compound
- Block pattern design
- Reinforced carcass and bead design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF318

Features

- Lug and block pattern design
- Special tread compound
- Reinforced carcass and bead design

Benefits

- Improved traction, driving and braking performance
- Provide outstanding resistance to puncture and tearing
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF320

Features

- Special tread compound
- Lug and block pattern design
- Reinforced carcass and bead design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance
- Ensure excellent handling and safe performance and provide outstanding loading capacity



Operation:

- Mostly used on rugged terrain like mining or heavy construction
- Heavier loads
- High risk of damage from road conditions

Size	HF168	HF707	HF318	HF320
7.00R16LT	118/114 K			
7.50R16LT	122/118 J			
8.25R16LT	128/124 J			
8.25R20	139/137 C		139/137 C	
9.00R20	144/142 C		144/142 C	
10.00R20	149/146 C	149/146 K	149/146 C	
11.00R20	152/149 D	152/149 K	152/149 C	
12.00R20	156/153 C	156/153 K	156/153 C	
12.00R24		160/157 F		
11R22.5		148/145 C		
12R22.5		152/149 D		
295/80R22.5		152/149 F	152/149 C	152/149 C
315/80R22.5			156/152 L(154/151 M)	



DRIVE/TRAILER



HF321

Features

- Lug and block pattern design
- Special tread compound
- Reinforced carcass and bead design

Benefits

- Improved traction, driving and braking performance
- Provide outstanding resistance to puncture and tearing
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF929

Features

- Lug and block pattern design
- Special tread compound
- Reinforced carcass and bead design

Benefits

- Improved traction, driving and braking performance
- Provide outstanding resistance to puncture and tearing
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF826

Features

- Lug and block pattern design
- Special tread compound
- Reinforced carcass and bead design

Benefits

- Improved traction, driving and braking performance
- Provide outstanding resistance to puncture and tearing
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF332

Features

- Lug and block pattern design
- Special tread compound
- Reinforced carcass and bead design

Benefits

- Improved traction, driving and braking performance
- Provide outstanding resistance to puncture and tearing
- Ensure excellent handling and safe performance and provide outstanding loading capacity

Size	HF321	HF929	HF826	HF332
7.50R16	122/118 L			
8.25R16	128/124 L			
8.25R20	139/137 K			
9.00R20	144/142 D			
10.00R20	149/146 D			
11.00R20	152/149 C	152/149 C		
12.00R20	156/153 C			
12.00R24	160/157 K		160/157 K	
11R22.5			149/146 L	148/145 J
11R24.5			149/146 K	149/146 K
295/80R22.5				



DRIVE/TRAILER



HF055

Features

- Special tread compound
- Lug and block pattern design
- Reinforced carcass and bead design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF591

Features

- Lug and block pattern design
- Special tread compound
- Reinforced carcass and bead design

Benefits

- Improved traction, driving and braking performance
- Provide outstanding resistance to puncture and tearing
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF519

Features

- Lug and block pattern design
- Special tread compound
- Reinforced carcass and bead design

Benefits

- Improved traction, driving and braking performance
- Provide outstanding resistance to puncture and tearing
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF056

Features

- Lug and block pattern design
- Special tread compound
- Reinforced carcass and bead design

Benefits

- Improved traction, driving and braking performance
- Provide outstanding resistance to puncture and tearing
- Ensure excellent handling and safe performance and provide outstanding loading capacity

Size	HF055	HF591	HF519	HF056
12R22.5	152/149 F			
12.00R20		158/155 F	158/155 F	158/155 D

PRODUCT RANGE



									
DIMENSION		HF708	HF117	HF599+	HF599	HF330	HF660	HF606	HF606+
7.50R16LT	16PR				125/121 L				
8.25R16	16PR								
9.00R20	16PR	144/142 K						144/142 K	
10.00R20	18PR	149/146 K						149/146 K	
11.00R20	18PR	152/149 K		152/149 J	152/149 K			152/149 K	
12.00R20	20PR	156/153 K						156/153 K	
12.00R24	20PR	160/157 K							
9.5R17.5	16PR								
11R22.5	16PR					148/145 M	148/145 M	148/145 M	
12R22.5	18PR		152/149 L			152/149 M	152/149 M		
13R22.5	20PR					156/152 L(154/151 M)			
11R24.5	14PR								
11R24.5	16PR								
215/75R17.5	16PR						135/133 J		
235/75R17.5	16PR								
225/70R19.5	14PR								
245/70R19.5	16PR								
255/70R22.5	16PR						140/137 L		
295/75R22.5	14PR								
295/75R22.5	16PR								
295/80R22.5	18PR						152/149 M		
315/70R22.5	20PR						154/150 L(152/148 M)		
315/80R22.5	20PR						156/152 L(154/151 M)		156/152 L(154/151 M)
285/75R24.5	14PR								
285/75R24.5	16PR								

									
HF688	HF111	HF121	HF123	HF124	HF680	HF127	HF788	HF689	HF061
						125/121 L			
		152/149 K	152/149 K						
								160/157 K	
		143/141 J							
	146/143 L								
									152/149 L
	146/143 M								
	149/146 L								
	135/133 J								
	143/141 J								
	128/126 L								
	135/133 L								
	140/137 L								
	144/141 M								
	146/143 L								
152/149 M		152/149 M					152/149 M		
		154/150 L(152/148 M)							
		156/152 L(154/151 M)		156/152 L(154/151 M)	156/152 L(154/151 M)				
	144/141 M								
	147/144 L								

PRODUCT RANGE



									
DIMENSION		HF976	HF979	HF192	HF571	HF661	HF685	HF122	HF668
9.00R20	18PR								
10.00R20	18PR								149/146 K
11.00R20	18PR								
12.00R20	20PR								
12.00R24	20PR							160/157 K	
11R22.5	16PR								
12R22.5	18PR	152/149 L	152/149 L	152/149 L	152/149 L	152/149 L			
13R22.5	20PR								
11R24.5	14PR								
11R24.5	16PR								
215/75R17.5	16PR								
235/75R17.5	16PR								
295/75R22.5	14PR								
295/75R22.5	16PR								
295/80R22.5	18PR						152/149 M		152/149 M
315/70R22.5	20PR								
315/80R22.5	20PR							156/152 L(154/151 M)	
285/75R24.5	14PR								
285/75R24.5	16PR								

									
HF628	HF607	HF312	HF638	HF505	HF323	HF326	HF328	HF331	HF616
			144/142 K						144/142 K
			149/146 K	149/146 D					149/146 K
									156/153 K
	160/157 K								
148/145 M		146/143 L	148/145 M		146/143 L				
152/149 M			152/149 M						
156/152 L(154/151 M)									
		146/143 M			146/143 M				
		149/146 L			149/146 L				
135/133 J									
143/141 J									
		144/141 M			144/141 M				
		146/143 L			146/143 L				
152/149 M						152/149 M			
154/150 L(152/148 M)			154/150 L(152/148 M)			154/150 L(152/148 M)			
156/152 L(154/151 M)			156/152 L(154/151 M)			156/152 L(154/151 M)	156/152 L(154/151 M)	156/152 L(154/151 M)	
		144/141 M			144/141 M				
		147/144 L			147/144 L				

PRODUCT RANGE



								
DIMENSION		HF626	HF638+	HF327	HF051	HF081	HF565	HF391
9.00R20	18PR							
10.00R20	18PR	149/146 K						
11.00R20	18PR	152/149 K						
12.00R20	20PR							156/153 J
12.00R24	20PR							
11R22.5	16PR							
12R22.5	18PR		152/149 M		152/149 K	152/149 L	152/149 L	
13R22.5	20PR							
11R24.5	14PR							
11R24.5	16PR							
215/75R17.5	16PR							
235/75R17.5	16PR							
295/75R22.5	14PR							
295/75R22.5	16PR							
295/80R22.5	18PR							
315/70R22.5	20PR							
315/80R22.5	20PR		156/152 L (154/151 M)					
285/75R24.5	14PR							
285/75R24.5	16PR							
285/75R24.5	20PR							
385/55R22.5	24PR							
385/65R22.5	24PR							

							
HF533	HF538	HF806	ST022	HF618	HF126	ST026	
				148/145 M	146/143 L	148/145 M	
				152/149 M			
					149/146 L		
			143/141 J				
				144/141 M			
				146/143 L	146/143 L		
152/149 M	152/149 M	152/149 M				152/149 M	
156/150 L (154/150 M)	156/150 L (154/150 M)					156/150 L (154/150 M)	
156/152 L (154/151 M)						156/152 L (154/151 M)	
					147/144 L		
						164 K	
			160 K			164 K	

PRODUCT RANGE



Mixed Service

							
DIMENSION	HF702	ST011	HF307	RS HF572	HF573	HF708+	HF768
6.50R16LT 12PR	110/105 K						
7.00R16LT 14PR	118/114 M						
7.50R16LT 14PR	122/118 M						
8.25R16LT 16PR	128/124 M						
8.25R20 16PR	139/137 L						
9.00R20 16PR	144/142 K						
9.5R17.5 18PR				143/141 J			
10.00R20 18PR	149/146 K		149/146 K				149/146 D
11.00R20 18PR	152/149 K		152/149 K				152/149 J
12.00R20 20PR	156/153 K		156/153 K				156/153 J
12.00R24 20PR	160/157 K						
11R22.5 16PR	148/145 M						
12R22.5 18PR	152/149 M		152/149 L				152/149 M
13R22.5 20PR	156/152 L(154/151 M)				156/153 L		156/152 L(154/151 M)
11R24.5 16PR	149/146 L						
295/80R22.5 18PR							152/149 K
315/80R22.5 20PR		156/152 L(154/151 M)			156/152 L(154/151 M)	156/152 L(154/151 M)	
325/95R24 22PR				162/160 K			

							
HF706	HF701	HF313	HF322	HF729	HF303	HF325	HF768W
118/114 M					118/114 K		
122/118 M					122/118 J		
128/124 M		128/124 M			128/124 J		
139/137 L		139/137 K			139/137 K		
144/142 K	144/142 K	144/142 K			144/142 J		
149/146 K	149/146 K	149/146 K		149/146 K	149/146 J		
152/149 K	152/149 K	152/149 K			152/149 J		
156/153 K	156/153 K	156/153 K			156/153 J		
			160/157 K	160/157 K		160/157 K	
	148/145 L			148/145 L			
	152/149 M						
							156/152 L(154/151 M)

PRODUCT RANGE



Dimension		HF399	RS HF373	HF556	HF557	HF335	HF336	
6.50R16LT	12PR							
7.00R16LT	14PR							
7.50R16LT	14PR							
8.25R16LT	16PR							
8.25R20	16PR							
9.00R20	16PR	144/142 K						
9.5R17.5	18PR					143/141 J		
10.00R20	18PR	149/146 K						
11.00R20	18PR	152/149 K						
12.00R20	20PR	156/153 K						
12.00R24	20PR							
11R22.5	16PR							
12R22.5	18PR							
13R22.5	20PR						156/153 L	
11R24.5	16PR							
295/80R22.5	18PR			152/149 M	152/149 M			
315/80R22.5	20PR			156/152 L (154/151 M)	156/152 L (154/151 M)			
325/95R24	22PR		162/160 K					



Mixed Service

[illegible]

PRODUCT RANGE



								
DIMENSION		HF168	HF707	HF318	HF320	HF321	HF929	HF826
7.00R16LT	14PR	118/114 K						
7.50R16LT	14PR	122/118 J				122/118 L		
8.25R16LT	16PR	128/124 J				128/124 L		
8.25R20	16PR	139/137 C		139/137 C		139/137 K		
9.00R20	16PR	144/142 C		144/142 C		144/142 D		
10.00R20	18PR	149/146 C	149/146 K	149/146 C		149/146 D		
11.00R20	18PR	152/149 D	152/149 K	152/149 C		152/149 C	152/149 C	
12.00R20	20PR	156/153 C	156/153 K	156/153 C		156/153 C		
12.00R20	22PR							
12.00R24	20PR		160/157 F			160/157 K		160/157 K
11R22.5	18PR		148/145 C					149/146 L
11R24.5	16PR							149/146 K
11R24.5	18PR							
12R22.5	18PR		152/149 D					
295/80R22.5	18PR		152/149 F	152/149 C	152/149 C			
315/80R22.5	20PR			156/152 L(154/151 M)				

							
HF332	HF055	HF591	HF519	HF056			
		158/155 F	158/155 F	158/155 D			
148/145 J							
149/146 K							
	152/149 F						

Technical File

Size	PR	Width	A/R	Rim	LOAD INDEX	SPEED RATING	PATTERN	M+S	APPLICATION	STANDARD RIM	MAX LOAD(KG) SINGLE	MAX LOAD(KG) DUAL	MAX PRESSURE(KPA) SINGLE	MAX PRESSURE(KPA) DUAL	TREAD DEPTH (mm)	SECTION WIDTH (mm)	OUTER DIAMETER (mm)
6.50R16LT	12	6.5		16	110/105	K	HF702	M+S	M	5.50F	1150	1030	770	770	11.0	185	750
7.00R16LT	14	7		16	118/114	K	HF168	M+S	O	5.50F	1320	1180	770	770	15.5	200	775
7.00R16LT	14	7		16	118/114	M	HF702	M+S	M	5.50F	1320	1180	770	770	12.0	200	775
7.00R16LT	14	7		16	118/114	K	HF303	M+S	M	5.50F	1320	1180	770	770	14.0	200	775
7.00R16LT	14	7		16	118/114	M	HF706	M+S	M	5.50F	1320	1180	770	770	14.0	200	775
7.50R16LT	14	7.5		16	122/118	J	HF168	M+S	O	6.00G	1500	1320	770	770	16.5	215	805
7.50R16LT	14	7.5		16	122/118	M	HF702	M+S	M	6.00G	1500	1320	770	770	13	215	805
7.50R16LT	14	7.5		16	122/118	J	HF303	M+S	M	6.00G	1500	1320	770	770	15	215	805
7.50R16LT	14	7.5		16	122/118	M	HF706	M+S	M	6.00G	1500	1320	770	770	14	215	805
7.50R16LT	14	7.5		16	122/118	M	HF313	M+S	M	6.00G	1500	1320	770	770	15	215	805
7.50R16LT	14	7.5		16	122/118	L	HF321	M+S	M	6.00G	1500	1320	770	770	16.5	210	809
7.50R16LT	16	7.50		16	125/121	L	HF127	M+S	L&R	6.00G	1650	1450	870	870	12	215	805
7.50R16LT	16	7.50		16	125/121	L	HF599	M+S	L&R	6.00G	1650	1450	870	870	12	315	1226
8.25R16LT	16	8.25		16	128/124	M	HF168	M+S	M	6.50H	1800	1600	770	770	16	235	855
8.25R16LT	16	8.25		16	128/124	J	HF702	M+S	M	6.50H	1800	1600	770	770	16	235	855
8.25R16LT	16	8.25		16	128/124	M	HF303	M+S	M	6.50H	1800	1600	770	770	15	235	855
8.25R16LT	16	8.25		16	128/124	M	HF706	M+S	M	6.50H	1800	1600	770	770	16	235	855
8.25R16LT	16	8.25		16	128/124	L	HF321	M+S	M	6.50H	1800	1600	770	770	16.5	230	860
8.25R20	16	8.25		20	139/137	C	HF168	M+S	O	6.5	2430	2300	930	930	21	236	974
8.25R20	16	8.25		20	139/137	L	HF702	M+S	M	6.5	2430	2300	930	930	13.5	236	974
8.25R20	16	8.25		20	139/137	K	HF303	M+S	M	6.5	2430	2300	930	930	16	236	974
8.25R20	16	8.25		20	139/137	L	HF706	M+S	M	6.5	2430	2300	930	930	14.5	236	974
8.25R20	16	8.25		20	139/137	K	HF313	M+S	M	6.5	2430	2300	930	930	16	236	974
8.25R20	16	8.25		20	139/137	C	HF318	M+S	O	6.5	2430	2300	930	930	16	236	974
8.25R20	16	8.25		20	139/137	K	HF321	M+S	O	6.5	2430	2300	930	930	18	236	974
9.00R20	16	9		20	144/142	K	HF638	M+S	L&R	7.0	2800	2650	900	900	17	259	1019
9.00R20	16	9		20	144/142	K	HF606	M+S	L&R	7.0	2800	2650	900	900	15	259	1019
9.00R20	16	9		20	144/142	K	HF708	M+S	L&R	7.0	2800	2650	900	900	15	259	1019
9.00R20	16	9		20	144/142	C	HF168	M+S	O	7.0	2800	2650	900	900	21.5	259	1019
9.00R20	16	9		20	144/142	K	HF702	M+S	M	7.0	2800	2650	900	900	15.5	259	1019
9.00R20	16	9		20	144/142	J	HF303	M+S	M	7.0	2800	2650	900	900	17	259	1019
9.00R20	16	9		20	144/142	K	HF706	M+S	M	7.0	2800	2650	900	900	16	259	1019
9.00R20	16	9		20	144/142	K	HF701	M+S	M	7.0	2800	2650	900	900	16.5	259	1019
9.00R20	16	9		20	144/142	K	HF313	M+S	M	7.0	2800	2650	900	900	17	259	1019
9.00R20	16	9		20	144/142	C	HF318	M+S	M	7.0	2800	2650	900	900	17	258	1018
9.00R20	16	9		20	144/142	K	HF616	M+S	L&R	7.0	2800	2650	900	900	16	260	1019
9.00R20	16	9		20	144/142	K	HF399	M+S	M	7.0	2800	2650	900	900	18	260	1023
9.00R20	16	9		20	144/142	D	HF321	M+S	M	7.0	2800	2650	900	900	20	260	1027
10.00R20	18	10		20	149/146	K	HF606	M+S	L&R	7.5	3250	3000	930	930	15	278	1054
10.00R20	18	10		20	149/146	K	HF708	M+S	L&R	7.5	3250	3000	930	930	16.5	278	1054
10.00R20	18	10		20	149/146	C	HF168	M+S	O	7.5	3250	3000	930	930	22	278	1054
10.00R20	18	10		20	149/146	K	HF702	M+S	M	7.5	3250	3000	930	930	16.5	278	1054
10.00R20	18	10		20	149/146	K	HF768	M+S	M	7.5	3250	3000	930	930	18	278	1054
10.00R20	18	10		20	149/146	J	HF303	M+S	M	7.5	3250	3000	930	930	18	278	1054
10.00R20	18	10		20	149/146	K	HF706	M+S	M	7.5	3250	3000	930	930	17	278	1054
10.00R20	18	10		20	149/146	K	HF638	M+S	L&R	7.5	3250	3000	930	930	22	278	1054
10.00R20	18	10		20	149/146	K	HF701	M+S	M	7.5	3250	3000	930	930	17	278	1054
10.00R20	18	10		20	149/146	K	HF313	M+S	M	7.5	3250	3000	930	930	18	278	1054
10.00R20	18	10		20	149/146	K	HF707	M+S	O	7.5	3250	3000	930	930	20.5	278	1065
10.00R20	18	10		20	149/146	C	HF318	M+S	O	7.5	3250	3000	930	930	18	278	1054
10.00R20	18	10		20	149/146	K	HF688	M+S	L&R	7.5	3250	3000	930	930	21	278	1054
10.00R20	18	10		20	149/146	K	HF505	M+S	L&R	7.5	3250	3000	930	930	20.5	278	1054
10.00R20	18	10		20	149/146	K	HF616	M+S	L&R	7.5	3250	3000	930	930	16.5	276	1049
10.00R20	18	10		20	149/146	K	HF626	M+S	L&R	7.5	3250	3000	930	930	15	276	1046
10.00R20	18	10		20	149/146	K	HF399	M+S	M	7.5	3250	3000	930	930	19	276	1054
10.00R20	18	10		20	149/146	D	HF321	M+S	M	7.5	3250	3000	930	930	16.5	276	1049
11.00R20	18	11		20	152/149	K	HF606	M+S	L&R	8.0	3550	3250	930	930	17	293	1085

Technical File

Size	PR	Width	A/R	Rim	LOAD INDEX	SPEED RATING	PATTERN	M+S	APPLICATION	STANDARD RIM	MAX LOAD(KG) SINGLE	MAX LOAD(KG) DUAL	MAX PRESSURE(KPA) SINGLE	MAX PRESSURE(KPA) DUAL	TREAD DEPTH (mm)	SECTION WIDTH (mm)	OUTER DIAMETER (mm)
11.00R20	18	11		20	152/149	K	HF708	M+S	L&R	8.0	3550	3250	930	930	17	293	1085
11.00R20	18	11		20	152/149	K	HF121	M+S	L&R	8.0	3550	3250	930	930	15.5	293	1085
11.00R20	18	11		20	152/149	K	HF123	M+S	L&R	8.0	3550	3250	930	930	16.5	293	1085
11.00R20	18	11		20	152/149	K	HF702	M+S	M	8.0	3550	3250	930	930	17	293	1085
11.00R20	18	11		20	152/149	J	HF768	M+S	M	8.0	3550	3250	930	930	18	293	1085
11.00R20	18	11		20	152/149	J	HF303	M+S	M	8.0	3550	3250	930	930	19	293	1085
11.00R20	18	11		20	152/149	K	HF706	M+S	M	8.0	3550	3250	930	930	17.5	293	1085
11.00R20	18	11		20	152/149	K	HF307	M+S	M	8.0	3550	3250	930	930	17.5	293	1085
11.00R20	18	11		20	152/149	K	HF701	M+S	M	8.0	3550	3250	930	930	18	293	1085
11.00R20	18	11		20	152/149	K	HF313	M+S	M	8.0	3550	3250	930	930	19	293	1085
11.00R20	18	11		20	152/149	K	HF707	M+S	O	8.0	3550	3250	930	930	21	293	1085
11.00R20	18	11		20	152/149	C	HF318	M+S	O	8.0	3550	3250	930	930	24	293	1085
11.00R20	18	11		20	152/149	C	HF321	M+S	O	8.0	3550	3250	930	930	24	293	1085
11.00R20	18	11		20	152/149	J	HF599+	M+S	L&R	8.0	3550	3250	930	930	17.5	293	1085
11.00R20	18	11		20	152/149	K	HF599	M+S	L&R	8.0	3550	3250	930	930	16.5	288	1083
11.00R20	18	11		20	152/149	K	HF626	M+S	M	8.0	3550	3250	930	930	15.5	276	1046
11.00R20	18	11		20	152/149	K	HF399	M+S	M	8.0	3550	3250	930	930	20	288	1088
11.00R20	18	11		20	152/149	C	HF929	M+S	O	8.0	3550	3250	930	930	27.5	288	1106
11.00R20	18	11		20	152/149	D	HF168	M+S	O	8.0	3550	3250	930	930	16.5	293	1085
12.00R20	20	12		20	156/153	K	HF606	M+S	L&R	8.5	3750	3450	830	830	17.5	315	1125
12.00R20	20	12		20	156/153	K	HF708	M+S	L&R	8.5	3750	3450	830	830	17.5	315	1125
12.00R20	20	12		20	156/153	C	HF168	M+S	O	8.5	3750	3450	830	830	24	315	1136
12.00R20	20	12		20	156/153	K	HF702	M+S	M	8.5	3750	3450	830	830	17.5	315	1125
12.00R20	20	12		20	156/153	J	HF768	M+S	M	8.5	3750	3450	830	830	20	315	1125
12.00R20	20	12		20	156/153	J	HF303	M+S	M	8.5	3750	3450	830	830	20	315	1125
12.00R20	20	12		20	156/153	K	HF706	M+S	M	8.5	3750	3450	830	830	18.5	315	1125
12.00R20	20	12		20	156/153	K	HF307	M+S	M	8.5	3750	3450	830	830	18	315	1125
12.00R20	20	12		20	156/153	K	HF701	M+S	M	8.5	3750	3450	830	830	19	315	1125
12.00R20	20	12		20	156/153	K	HF313	M+S	M	8.5	3750	3450	830	830	20	315	1125
12.00R20	20	12		20	156/153	K	HF707	M+S	O	8.5	3750	3450	830	830	21.5	315	1125
12.00R20	20	12		20	156/153	C	HF318	M+S	O	8.5	3750	3450	830	830	25	315	1136
12.00R20	20	12		20	156/153	C	HF321	M+S	O	8.5	3750	3450	830	830	25	315	1136
12.00R20	20	12		20	156/153	K	HF616	M+S	L&R	8.5	4000	3650	900	900	18.5	310	1122
12.00R20	20	12		20	156/153	K	HF399	M+S	M	8.5	4000	3650	900	900	21	310	1130
12.00R20	20	12		20	156/153	J	HF391	M+S	L&R	8.5	4000	3650	900	900	21.5	315	1136
12.00R20	22	12		20	158/155	F	HF591	M+S	O	8.5	4250	3875	970	970	25	315	1136
12.00R20	22	12		20	158/155	F	HF519	M+S	O	8.5	4250	3875	970	970	26.5	315	1136
12.00R20	22	12		20	158/155	D	HF056	M+S	O	8.5	4250	3875	970	970	24.5	315	1136
12.00R24	20	12		24	160/157	K	HF122	M+S	L&R	8.5	4500	4125	900	900	15.5	315	1125
12.00R24	20	12		24	160/157	K	HF702	M+S	M	8.5	4500	4125	900	900	16	315	1125
12.00R24	20	12		24	160/157	K	HF607	M+S	L&R	8.5	4500	4125	900	900	20	315	1125
12.00R24	20	12		24	160/157	K	HF322	M+S	M	8.5	4500	4125	900	900	16	315	1125
12.00R24	20	12		24	160/157	K	HF729	M+S	M	8.5	4500	4125	900	900	19	315	1125
12.00R24	20	12		24	160/157	K	HF325	M+S	M	8.5	4500	4125	900	900	18.5	315	1226
12.00R24	20	12		24	160/157	F	HF707	M+S	M	8.5	4500	4125	900	900	18.5	236	1226
12.00R24	20	12		24	160/157	K	HF689	M+S	L&R	8.5	4500	4125	900	900	16	315	1216
12.00R24	20	12		24	160/157	K	HF826	M+S	O	8.5	4500	4125	900	900	24	238	1231
12.00R24	20	12		24	160/157	K	HF708	M+S	O	8.5	4500	4125	900	900	16	315	1226
11R22.5	16	11		22.5	148/145	M	HF330	M+S	L&R	8.25	3150	2900	850	850	15	279	1054
11R22.5	16	11		22.5	148/145	M	HF660	M+S	L&R	8.25	3150	2900	850	850	15	279	1054
11R22.5	16	11		22.5	148/145	M	HF606	M+S	L&R	8.25	3150	2900	850	850	15	279	1054
11R22.5	16	11		22.5	146/143	L	HF111	M+S	L&R	8.25	3000	2725	830	830	15	279	1054
11R22.5	16	11		22.5	148/145	M	HF618	M+S	L&R	8.25	3150	2900	850	850	11.5	279	1054
11R22.5	16	11		22.5	148/145	M	HF702	M+S	M	8.25	3150	2900	850	850	15.5	279	1054
11R22.5	16	11		22.5	148/145	M	HF638	M+S	L&R	8.25	3150	2900	850	850	20	279	1054
11R22.5	16	11		22.5	148/145	M	HF628	M+S	L&R	8.25	3150	2900	850	850	16.5	279	1054
11R22.5	16	11		22.5	146/143	L	HF312	M+S	L&R	8.25	3000	2725	830	830	21.5	279	1065
11R22.5	16	11		22.5	148/145	L	HF729	M+S	M	8.25	3000	2725	830	830	16.5	279	1065
11R22.5	16	11		22.5	146/143	L	HF323	M+S	L&R	8.25	3000	2725	830	830	21.5	279	1065
11R22.5	16	11		22.5	146/143	L	HF126	M+S	L&R	8.25	3000	2725	830	830	10	279	1054
11R22.5	16	11		22.5	146/143	M	HF826	M+S	O	8.25	3000	2725	830	830	22.5	273	1058
11R22.5	16	11		22.5	148/145	J	HF322	M+S	O	8.25	3150	2900	850	850	24.5	279	1065
11R22.5	16	11		22.5	148/145	C	HF707	M+S	O	8.25	3150	2900	850	850	20	279	1054
11R22.5	16	11		22.5	148/145	L	HF701	M+S	O	8.25	3150	2900	850	850	16.5	279	1054

Technical File

Size	PR	Width	A/R	Rim	LOAD INDEX	SPEED RATING	PATTERN	M+S	APPLICATION	STANDARD RIM	MAX LOAD(KG) SINGLE	MAX LOAD(KG) DUAL	MAX PRESSURE(KPA) SINGLE	MAX PRESSURE(KPA) DUAL	TREAD DEPTH (mm)	SECTION WIDTH (mm)	OUTER DIAMETER (mm)
11R22.5	16	11		22.5	148/145	M	ST026	M+S	L&R	8.25	3150	2900	850	850	15	279	1054
12R22.5	18	12		22.5	152/149	M	HF330	M+S	L&R	9.00	3550	3250	930	930	16.5	300	1085
12R22.5	18	12		22.5	152/149	M	HF660	M+S	L&R	9.00	3550	3250	930	930	16.5	300	1085
12R22.5	18	12		22.5	152/149	L	HF117	M+S	L&R	9.00	3550	3250	930	930	16	300	1085
12R22.5	18	12		22.5	152/149	M	HF618	M+S	L&R	9.00	3550	3250	930	930	12.5	300	1085
12R22.5	18	12		22.5	152/149	M	HF702	M+S	M	9.00	3550	3250	930	930	16	300	1085
12R22.5	18	12		22.5	152/149	M	HF768	M+S	M	9.00	3550	3250	930	930	20	300	1085
12R22.5	18	12		22.5	152/149	L	HF307	M+S	M	9.00	3550	3250	930	930	16	300	1085
12R22.5	18	12		22.5	152/149	M	HF628	M+S	L&R	9.00	3550	3250	930	930	17.5	300	1085
12R22.5	18	12		22.5	152/149	M	HF701	M+S	M	9.00	3550	3250	930	930	18.5	300	1085
12R22.5	18	12		22.5	152/149	M	HF638+	M+S	L&R	9.00	3550	3250	930	930	20	302	1087
12R22.5	18	12		22.5	152/149	D	HF707	M+S	L&R	9.00	3550	3250	930	930	19	300	1085
12R22.5	18	12		22.5	152/149	F	HF055	M+S	O	9.00	3550	3250	930	930	25	300	1096
12R22.5	18	12		22.5	152/149	K	HF051	M+S	L&R	9.00	3550	3250	930	930	21.5	300	1096
12R22.5	18	12		22.5	152/149	L	HF081	M+S	L&R	9.00	3550	3250	930	930	18	300	1085
12R22.5	18	12		22.5	152/149	L	HF081	M+S	L&R	9.00	3550	3250	930	930	18	300	1085
12R22.5	18	12		22.5	152/149	L	HF976	M+S	L&R	9.00	3550	3250	930	930	16	300	1085
12R22.5	18	12		22.5	152/149	L	HF979	M+S	L&R	9.00	3550	3250	930	930	16	300	1085
12R22.5	18	12		22.5	152/149	L	HF192	M+S	L&R	9.00	3550	3250	930	930	18	300	1085
12R22.5	18	12		22.5	152/149	L	HF565	M+S	L&R	9.00	3550	3250	930	930	18	300	1085
12R22.5	18	12		22.5	152/149	L	HF571	M+S	L&R	9.00	3550	3250	930	930	16.5	300	1085
12R22.5	18	12		22.5	152/149	L	HF661	M+S	L&R	9.00	3550	3250	930	930	16	300	1085
13R22.5	20	13		22.5	156/152(154/151)	L(M)	HF660	M+S	L&R	9.75	4000	3550	860	860	17	320	1124
13R22.5	20	13		22.5	156/152(154/151)	L(M)	HF702	M+S	M	9.75	4000	3550	860	860	16.5	320	1124
13R22.5	20	13		22.5	156/152(154/151)	L(M)	HF768	M+S	M	9.75	4000	3550	860	860	20	320	1124
13R22.5	20	13		22.5	156/152(154/151)	L(M)	HF628	M+S	L&R	9.75	4000	3550	860	860	18	320	1124
13R22.5	20	13		22.5	156/153	L	HF336	M+S	M	9.75	4000	3650	930	930	19	320	1124
13R22.5	20	13		22.5	156/153	L	HF573	M+S	M	9.75	4000	3650	930	930	17	320	1124
11R24.5	14	11		24.5	146/143	M	HF111	M+S	L&R	8.25	3000	2725	720	720	15	279	1104
11R24.5	14	11		24.5	146/143	M	HF312	M+S	L&R	8.25	3000	2725	720	720	21.5	279	1104
11R24.5	14	11		24.5	146/143	M	HF323	M+S	L&R	8.25	2800	2575	760	760	22	283	1062
11R24.5	16	11		24.5	149/146	L	HF111	M+S	L&R	8.25	3250	3000	830	830	15	279	1104
11R24.5	16	11		24.5	149/146	L	HF702	M+S	M	8.25	3250	3000	830	830	15.5	279	1104
11R24.5	16	11		24.5	149/146	L	HF312	M+S	L&R	8.25	3250	3000	830	830	21.5	279	1104
11R24.5	16	11		24.5	149/146	L	HF323	M+S	M	8.25	3250	3000	830	830	21.5	279	1116
11R24.5	16	11		24.5	149/146	L	HF126	M+S	M	8.25	3250	3000	830	830	10	302	1104
11R24.5	16	11		24.5	149/146	K	HF332	M+S	O	8.25	3250	3000	830	830	24.5	284	1114.5
11R24.5	18	11		24.5	152/149	K	HF826	M+S	O	8.25	3550	3250	930	930	20.5	279	1104
215/75R17.5	16	215	75	17.5	135/133	J	HF660	M+S	L&R	6.00	2180	2060	850	850	12	212	767
215/75R17.5	16	215	75	17.5	135/133	J	HF111	M+S	L&R	6.00	2180	2060	850	850	13	212	767
215/75R17.5	16	215	75	17.5	135/133	J	HF628	M+S	L&R	6.00	2180	2060	850	850	14	212	767
235/75R17.5	16	235	75	17.5	143/141	J	ST022	M+S	L&R	6.75	2725	2575	875	875	13	233	797
235/75R17.5	16	235	75	17.5	143/141	J	HF111	M+S	L&R	6.75	2725	2575	875	875	13	233	797
235/75R17.5	16	235	75	17.5	143/141	J	HF628	M+S	L&R	6.75	2725	2575	875	875	15	233	797
225/70R19.5	14	225	70	19.5	128/126	L	HF111	M+S	L&R	6.75	1800	1700	760	760	13	226	811
245/70R19.5	16	245	70	19.5	135/133	L	HF111	M+S	L&R	7.50	2180	2060	830	830	13	248	839
255/70R22.5	16	255	70	22.5	140/137	L	HF660	M+S	L&R	7.50	2500	2300	830	830	14	255	930
255/70R22.5	16	255	70	22.5	140/137	L	HF111	M+S	L&R	7.50	2500	2300	830	830	13	255	930
295/75R22.5	14	295	75	22.5	144/141	M	HF111	M+S	L&R	9.00	2800	2575	760	760	15.5	298	1014
295/75R22.5	14	295	75	22.5	144/141	M	HF312	M+S	L&R	9.00	2800	2575	760	760	22	298	1026
295/75R22.5	14	295	75	22.5	144/141	M	HF618	M+S	L&R	9.00	2800	2575	760	760	11	298	1014
295/75R22.5	14	295	75	22.5	144/141	M	HF323	M+S	L&R	9.00	2800	2575	760	760	22	298	1026
295/75R22.5	16	295	75	22.5	146/143	L	HF111	M+S	L&R	9.00	3000	2725	830	830	15.5	298	1014
295/75R22.5	16	295	75	22.5	146/143	L	HF312	M+S	L&R	9.00	3000	2725	830	830	22	298	1026
295/75R22.5	16	295	75	22.5	146/143	L	HF618	M+S	L&R	9.00	3000	2725	830	830	11	298	1014
295/75R22.5	16	295	75	22.5	146/143	L	HF323	M+S	L&R	9.00	3000	2725	830	830	22	298	1026
295/75R22.5	16	295	75	22.5	146/143	L	HF126	M+S	L&R	9.00	3000	2725	830	830	10	298	1014
295/80R22.5	18	295	80	22.5	152/149	C	HF320	M+S	O	9.00	3550	3250	900	900	21.5	298	1044
295/80R22.5	18	295	80	22.5	152/149	M	HF121	M+S	L&R	9.00	3550	3250	900	900	16.5	298	1044
295/80R22.5	18	295	80	22.5	152/149	M	HF660	M+S	L&R	9.00	3550	3250	900	900	15	298	1044

Technical File

Size	PR	Width	A/R	Rim	LOAD INDEX	SPEED RATING	PATTERN	M+S	APPLICATION	STANDARD RIM	MAX LOAD(KG) SINGLE	MAX LOAD(KG) DUAL	MAX PRESSURE(KPA) SINGLE	MAX PRESSURE(KPA) DUAL	TREAD DEPTH (mm)	SECTION WIDTH (mm)	OUTER DIAMETER (mm)
295/80R22.5	18	295	80	22.5	152/149	M	HF688	M+S	L&R	9.00	3550	3250	900	900	15	298	1044
295/80R22.5	18	295	80	22.5	152/149	M	HF628	M+S	L&R	9.00	3550	3250	900	900	20.5	298	1044
295/80R22.5	18	295	80	22.5	152/149	C	HF318	M+S	O	9.00	3550	3250	900	900	21.5	298	1044
295/80R22.5	18	295	80	22.5	152/149	M	HF668	M+S	L&R	9.00	3550	3250	900	900	18	298	1044
295/80R22.5	18	295	80	22.5	152/149	M	HF326	M+S	L&R	9.00	3550	3250	900	900	17.5	298	1044
295/80R22.5	18	295	80	22.5	152/149	M	HF788	M+S	L&R	9.00	3550	3250	900	900	18	292	1047
295/80R22.5	18	295	80	22.5	152/149	M	HF826	M+S	O	9.00	3550	3250	900	900	24.5	292	1060
295/80R22.5	18	295	80	22.5	152/149	F	HF707	M+S	O	9.00	3550	3250	900	900	21.5	308	1050
295/80R22.5	18	295	80	22.5	152/149	K	HF768	M+S	M	9.00	3550	3250	900	900	21.5	298	1044
295/80R22.5	18	295	80	22.5	152/149	M	HF538	M+S	L&R	9.00	3550	3250	900	900	21	298	1050
295/80R22.5	18	295	80	22.5	152/149	M	HF556	M+S	M	9.00	3550	3250	900	900	21	298	1050
295/80R22.5	18	295	80	22.5	152/149	M	ST026	M+S	L&R	9.00	3550	3250	900	900	16	298	1044
295/80R22.5	18	295	80	22.5	152/149	M	HF557	M+S	M	9.00	3550	3250	900	900	21	298	1050
295/80R22.5	18	295	80	22.5	152/149	M	HF685	M+S	L&R	9.00	3550	3250	900	900	15.5	298	1044
295/80R22.5	18	295	80	22.5	152/149	M	HF533	M+S	L&R	9.00	3550	3250	900	900	20	298	1044
295/80R22.5	18	295	80	22.5	152/149	M	HF806	M+S	L&R	9.00	3550	3250	900	900	22.5	292	1047
315/70R22.5	20	315	70	22.5	154/150(152/148)	L(M)	HF660	M+S	L&R	9.00	3750	3350	900	900	15	312	1014
315/70R22.5	20	315	70	22.5	154/150(152/148)	L(M)	HF121	M+S	L&R	9.00	3750	3350	900	900	15.5	312	1014
315/70R22.5	20	315	70	22.5	154/150(152/148)	L(M)	HF638	M+S	L&R	9.00	3750	3350	900	900	20	312	1014
315/70R22.5	20	315	70	22.5	154/150(152/148)	L(M)	HF628	M+S	L&R	9.00	3750	3350	900	900	21	312	1014
315/70R22.5	20	315	70	22.5	154/150(152/148)	L(M)	HF326	M+S	L&R	9.00	3750	3350	900	900	19.5	312	1014
315/70R22.5	20	315	70	22.5	156/150(154/150)	L(M)	HF538	M+S	L&R	9.00	4000	3350	900	900	19.5	312	1020
315/70R22.5	20	315	70	22.5	156/150(154/150)	L(M)	HF533	M+S	L&R	9.00	4000	3350	900	900	18.5	312	1020
315/70R22.5	20	315	70	22.5	156/150(154/150)	L(M)	ST026	M+S	L&R	9.00	4000	3350	900	900	15.5	312	1014
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF660	M+S	L&R	9.00	4000	3550	860	860	14.5	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF606+	M+S	L&R	9.00	4000	3550	860	860	14.5	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF121	M+S	L&R	9.00	4000	3550	860	860	15.5	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF122	M+S	L&R	9.00	4000	3550	860	860	16.5	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF124	M+S	L&R	9.00	4000	3550	860	860	15.5	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	ST011	M+S	M	9.00	4000	3550	860	860	17.5	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF768	M+S	M	9.00	4000	3550	860	860	23	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF638	M+S	L&R	9.00	4000	3550	860	860	23	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF628	M+S	L&R	9.00	4000	3550	860	860	20	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF322	M+S	M	9.00	4000	3550	860	860	20.5	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF680	M+S	L&R	9.00	4000	3550	860	860	14.5	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF326	M+S	L&R	9.00	4000	3550	860	860	20	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF328	M+S	L&R	9.00	4000	3550	860	860	20	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF331	M+S	L&R	9.00	4000	3550	860	860	20	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF768W	M+S	M	9.00	4000	3550	860	860	23	312	1082
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF327	M+S	L&R	9.00	4000	3550	860	860	20	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF708+	M+S	M	9.00	4000	3550	860	860	17.5	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF318	M+S	M	9.00	4000	3550	860	860	23	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF556	M+S	M	9.00	4000	3550	860	860	23	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF557	M+S	M	9.00	4000	3550	860	860	23	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	HF533	M+S	L&R	9.00	4000	3550	860	860	23	312	1076
315/80R22.5	20	315	80	22.5	156/152(154/151)	L(M)	ST026	M+S	L&R	9.00	4000	3550	860	860	23	312	1076
385/55R22.5	24	385	55	22.5	164	K	ST026	M+S	L&R	12.25	5000	-	900	-	15	386	996
385/65R22.5	20	385	65	22.5	160	K	ST022	M+S	L&R	11.75	4500	-	900	-	17	389	1072
385/65R22.5	24	385	65	22.5	164	K	ST026	M+S	L&R	11.75	5000	-	900	-	16	389	1072
285/75R24.5	14	285	75	24.5	144/141	M	HF111		L&R	8.25	2800	2575	760	760	15.5	283	1050
285/75R24.5	14	285	75	24.5	144/141	M	HF312		L&R	8.25	2800	2575	760	760	22	283	1056
285/75R24.5	14	285	75	24.5	144/141	M	HF323	M+S	L&R	8.25	2800	2575	760	760	22	283	1062
285/75R24.5	16	285	75	24.5	147/144	L	HF111		L&R	8.25	3075	2800	830	830	15.5	283	1050
285/75R24.5	16	285	75	24.5	147/144	L	HF312		L&R	8.25	3075	2800	830	830	22	283	1056
285/75R24.5	16	285	75	24.5	147/144	L	HF323	M+S	L&R	8.25	3075	2800	830	830	22	283	1062
285/75R24.5	16	285	75	24.5	147/144	L	HF126	M+S	L&R	8.25	3075	2800	830	830	10	283	1050
325/95R24	22	325	95	24	162/160	K	RSHF572	M+S	M	8.5	4750	4500	850	850	17	325	1228
325/95R24	22	325	95	24	162/160	K	RSHF373	M+S	M	8.5	4750	4500	850	850	19	325	1228
9.5R17.5	16	9.5		17.5	143/141	J	HF121	M+S	L&R	6.75	2725	2575	875	875	13	240	842
9.5R17.5	18	9.5		17.5	143/141	J	HF335	M+S	M	6.75	2725	2575	875	875	16	240	842
9.5R17.5	18	9.5		17.5	143/141	J	HF572	M+S	M	6.75	2725	2575	875	875	15	240	842